



CROSS SECTION

NOTES:

1. THE REQUIRED DISTANCES FROM THE CURBS WILL APPLY TO UNDERGROUND UTILITIES.
2. THE REQUIRED LOCATION OF UTILITIES SHALL BE MEASURED FROM THE BACK OF THE CURB. CURB & GUTTER MUST BE INSTALLED AFTER SEWER BUT BEFORE ANY OTHER UTILITIES ARE INSTALLED.
3. PEDESTALS FOR TELEPHONE AND CABLE INSTALLATIONS TO BE LOCATED 6.5 FT. FROM BACK OF CURB.
4. FIRE HYDRANTS ON ROAD THRUWAYS ARE TO BE LOCATED A MINIMUM OF 5 FT. FROM BACK OF CURB. FIRE HYDRANTS ON CUL-DE-SACS ARE TO BE LOCATED A MAXIMUM OF 8 FT. FROM BACK OF CURB.
5. ELECTRICAL TRANSFORMERS ARE TO BE LOCATED IN LINE WITH DESIGNATED SPACE FOR POWER. STREET LIGHTS ARE TO BE LOCATED 7.5' FROM BACK OF CURB.
6. REAR OF WATER METER TO BE AT PROPERTY LINE.
7. SEWER SERVICE STUB TO EXTEND 5 FT. ONTO PROPERTY.

**CITY OF
EMERSON**
DEPARTMENT OF
PUBLIC WORKS

**NOMINAL UTILITY
LOCATIONS
50' R/W**
CONSTRUCTION STANDARD

DATE: SEPT. 2006

DATE: JUNE 2009

APPROVED:

STANDARD
NO.
3.8.12